

# LNX3

## 3-Inch Mobile Printer

Drive productivity, improve inventory management, and customer service by giving your workers a leading advantage in challenging work environments to help achieve your operational goals.

The LNX3 mobile label and receipt printer brings the power and reliability of Honeywell printers into a durable, lightweight, direct thermal printer meeting or exceeding industry printer specifications. This three-inch, feature-packed, high-capacity label and receipt printer gives the right technology for your business's rapidly changing work environments.

Compact enough to carry or wear during a full work shift, equipped with seamless Wi-Fi and Bluetooth® connectivity, and leading print speeds up to 5 IPS, this printer supports large-volume label and receipt printing requirements in longer intervals helping boost productivity. Keep printing through demanding environments with a long-lasting 2800mAH hot-swap battery allowing for extended operating and standby time.

Effortlessly connect with MFi, NFC pairing, and both Bluetooth and Wi-Fi options. Print from almost any device with Windows®, iOS, and Android™ compatibility.

Enable greater mobility and capability with optional accessories, including a IP54 case with belt clip or shoulder strap, battery charger, spare battery, and more.



*Durable, rugged direct thermal printer with intuitive set-up and interface for premium printing performance.*

## FEATURES AND BENEFITS



Certification to IP54, withstands tumbles up to 0.5 m (1.5 ft) and drops up to 1.8 m (5 ft) with protective case for maximum durability.



Powered by a 2800mAH hot-swap battery, easily swap the battery without losing connectivity or re-setting the printer.



MFi certified for iOS and Bluetooth, and NFC to conveniently connect to smart devices.



2.4-inch LED color screen and single hand media loading door design simplifies setup and maintenance.



Comprehensive printer command language support, such as ZPL-II, ESC/P, CPCL, XSim, ESC/POS, and more for easier printing.

# LNX3 Mobile Printer Technical Specifications

## MECHANICAL

### Dimensions:

137 mm L x 117 mm W x 55 mm H  
(5.31 in L x 4.53 in W x 2.05 in H)

**Weight:** 0.5 kg (1.1 lbs) (with paper roll and battery)

**Display Size:** 6.1 cm (2.4 in)

## ENVIRONMENTAL

Meets IP54 dust and water ingress rating

**Drop:** 1.8 m (6 ft) with protective case

**Tumble:** 1000 cycles at 0.5 m (1.6 ft)

**Operating Temperature:**

-15°C to 55°C (5°F to 131°F)

**Storage Temperature:**

-20°C to +70°C (-4°F to +158°F)

**Charging Temperature:**

0°C to 45°C (32°F to 113°F)

**Humidity:**

10% to 90%, non-condensing

## SYSTEM ARCHITECTURE

### Product:

LNX3-0: NFC, USB C, BT5.0

LNX3-1: NFC, USB C, BT5.0, Wi-Fi

**Printing Modes:** Direct thermal printing

**Processors:** Arm® Cortex®-A7, up to 792 MHz

### Memory:

RAM: 256 MB

Flash: 256 MB

### Standard Battery:

Rechargeable, removable, 7.4V Li-Ion, 2800mAh

Supports 1 minute hot swap

Integrated fuel gauge to monitor battery charge levels

Recharging: ≤3.5H

### Battery Endurance:

Bluetooth SKU: 118 m (387 ft)

Bluetooth & Wi-Fi SKU: 96 m (314 ft)

### Memory:

RAM: 256 MB

Flash: 256 MB

**AC Adapter:** 100 to 240 VAC 5VDC@2.0A

## PRINT AND MEDIA SPECIFICATIONS

**Printing Resolution:** 203 dpi (8 dots/mm)

**Printing Speed:** 50 - 127 mm/s (2-5 in per second)

**Media Roll Width:** 43 - 80 mm  
(1.7 - 3 in)

**Media Length:** 20 - 1016 mm (0.78 - 40 in)

**Maximum Roll Capacity:** 43 mm (1.69 in) outside diameter

**Media Thickness:** 0.06 - 0.18 mm  
(2 to 7 mils)

## CONNECTIVITY

### Standard:

USB 2.0, Type C

USB virtual COM port for diagnostic information

NFC, for quick pairing

Bluetooth 5.0 + BLE; Made for iPhone/iPad certified

### Optional:

Wi-Fi LAN 802.11 a/b/g/n and Bluetooth with dual radio mode

## SOFTWARE

**Programming Language:** ESC/P (Line print and easy print modes), ZPLII, CPCL, ESC/POS, XSim

- Yushi printer tool configuration utility
- SDKs for Android, iOS and Windows
- InterDriver printer drivers for Windows PCs

## CHARACTER SETS

### ESC/P (Easy Print, Line Print):

**Standard:** Arabic, Cyrillic, Greek, Thai and Hebrew

### CPCL

**Standard:** Latin

**Optional:** Simplified Chinese, traditional Chinese, Japanese, Korean, Arabic and Thai

### ZPL-II

**Standard:** Latin

**Optional:** Simplified Chinese, traditional Chinese, Japanese, Korean, Arabic and Thai

### XSim

**Standard:** Latin

**ESC/POS** Most Codepage

## SHIPS WITH

- Printer with standard battery
- Universal AC charger with USB cable
- Plastic belt clip
- Quick-start guide
- CD (printer driver and printer configuration tool)
- Regulatory sheet

## BARCODE SYBLOGIES/GRAPHICS

### ESC/P

**1D:** Code 39, Codabar, interleaved 2 of 5, code 128, EAN-18, UPC-A, EAN-8, EAN-13

**2D:** Aztec, PDF417, QR code

**Graphics:** Bitmap graphics, compressed graphics

### ZPL

**1D:** Code11, interleaved 2 of 5, code 39, EAN-8, UPC-E, code 93, code128, EAN-13, industrial 2 of 5, standard 2 of 5, ANSI Codebar, LOGMARS, MSI, Plessey, UPC/EAN Extensions, UPC-A

**2D:** Aztec, PDF417, UPS MaxiCode, QR code, data matrix

**Graphics:** Bitmap graphics, compressed graphics

### CPL

**1D:** Codabar, Code 39, Code 128, interleaved 2 of 5, UPC-A, UPC-E, EAN13, EAN8, EAN/JAN-13, EAN/JAN-8, Code 93/Ext. 93, I2OF5C, German post code, MSI/Plessey

**2D:** Aztec, PDF417, MaxiCode, QR code

**Graphics:** Bitmap graphics, compressed graphics

### XSim

**1D:** Codabar, code 39, code 128, EAN/UPC interleaved 2 of 5

**2D:** PDF417, QR code

**Graphics:** Bitmap graphics, compressed graphics

### ESC/POS

**1D:** UPC-A, UPC-E, EAN13, EAN8, code 39, interleaved 2 of 5, Codabar, code 93, code 128, code 11, MSI

**2D:** PDF417, MAXICODE, QR code

**Graphics:** Bitmap graphics

## ACCESSORIES

- Belt clip (in standard packing)
- Printer single charge base
- Quad battery charger
- Carrying case
- Spare battery
- Power adapter with USB cable (in standard packing)
- Adapter/12V-24V (vehicle battery charger)

For a complete listing of all compliance approvals and certifications, please visit [www.honeywell.com/PSScompliance](http://www.honeywell.com/PSScompliance)

For a complete listing of all supported barcode symbologies, please visit [www.honeywell.com/PSS-symbologies](http://www.honeywell.com/PSS-symbologies)

Apple, Android, iOS, iPhone, iPad, Windows, Bluetooth, and Arm Cortex are trademarks or registered trademarks of their respective owners.

## For more information

[sps.honeywell.com](http://sps.honeywell.com)

## Honeywell Safety and Productivity Solutions

855 S Mint St

Charlotte, NC 28202

800-582-4263

[www.honeywell.com](http://www.honeywell.com)